

Terblend® N NG-02 (Cond)

Polyamide 6 + ABS

BASF Corporation

Product Description

Terblend N NG-02 is a glass fibre reinforced ABS/PA6 blend with excellent dimensional stability, high impact strength and good surface appearance.

General

Material Status	• Commercial: Active
Availability	• North America
Filler / Reinforcement	• Glass Fiber Reinforcement, 8.0% Filler by Weight
Additive	• Antistatic
Features	• Antistatic • Good Dimensional Stability • Good Surface Finish
Agency Ratings	• ULC Unspecified Rating
RoHS Compliance	• RoHS Compliant
Forms	• Pellets
Processing Method	• Injection Molding

Mechanical	Nominal Value	Unit	Test Method
Tensile modulus	2400	MPa	ISO 527-2 ²
Tensile Stress (Break)	48.0	MPa	ISO 527-2 ²
Tensile Strain (Break)	4.0	%	ISO 527-2 ²

Hardness	Nominal Value	Unit	Test Method
Ball Indentation Hardness	83.0	MPa	ISO 2039-1

Notes

¹ Typical properties: these are not to be construed as specifications.

² Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.

Dongguan Yi-Ming Plastic Chemical Co., Ltd.

如需要更多物性资料请查阅 www.kedisujiao.com

备注：以上原料物性数据由厂家发布,我公司仅提供参考！数据如有变动，请联系原料生产厂家获知。我公司不承担任何法律责任！