

Ultramid® C 40LX 01

Polyamide 66/6 Copolymer

BASF Corporation

Product Description

Ultramid C40LX 01 is a high viscosity, copolymer PA6/66 grade. Improved transparency and gloss are enhanced by the incorporation of a high dose of lubricant. It conforms to FDA requirements including, 21 CFR 177.1500, EU Directive 2002/72/EC, the German BfR recommendation "X Polyamide", 1.6.1998 or legislations for other countries will be provided on request.

General

Material Status	• Commercial: Active	
Availability	• Europe	• North America
Additive	• Lubricant	
Features	• High Viscosity	• Lubricated
Uses	• Monofilaments	
Agency Ratings	• FDA 21 CFR 177.1500	
RoHS Compliance	• RoHS Compliant	
Appearance	• Natural Color	
Forms	• Pellets	
Processing Method	• Film Extrusion	

Physical	Nominal Value	Unit	Test Method
Density	1.12	g/cm ³	ISO 1183
Apparent Density	0.70	g/cm ³	ISO 60
Water Absorption			ISO 62 ²
Saturation	11	%	
Equilibrium	3.2	%	
Viscosity Number (96% H ₂ SO ₄)	250	cm ³ /g	ISO 307

Thermal	Nominal Value	Unit	Test Method
Melting Temperature (DSC)	190	°C	ISO 3146

Additional Information	Nominal Value	Unit	Test Method
Moisture Content	< 0.080	%	ISO 15512
Pellet Shape	cylindrical		
Pellet Size	2.00 to 2.50	mm	
Relative Viscosity (1% in 96% Sulfuric Acid)	4.00		ISO 307

Notes

¹ Typical properties: these are not to be construed as specifications.

² Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.

Dongguan Yi-Ming Plastic Chemical Co., Ltd.

如需要更多物性资料请查阅 www.kedisujiao.com

备注：以上原料物性数据由厂家发布,我公司仅提供参考！数据如有变动，请联系原料生产厂家获知。我公司不承担任何法律责任！